



[Ask a Question](#)

Key Product Features

- Brilliant visual alarm
- Ultra loud alarm - 95 dBA
- Plug 'n' Play sensor technology
- Robust, Hi-Viz, Hi-Impact resistance
- International certification & conformance

- [Overview](#)
- [Features](#)
- [Specification](#)
- [Applications](#)
- [Downloads](#)

A robust and accurate portable gas detector, the VISA provides unrivalled protection in confined space applications with audible and visual alarms in the event of exposure to flammable or toxic gases.

Detecting and displaying up to 5 gases simultaneously using "plug and play" sensor technology, the VISA is suitable for a host of applications in a variety of industries using infra-red, PID and catalytic sensors.

Pre-entry checking can be carried out with the optional internal sampling pump and diffusion operation, ensuring maximum battery life in confined spaces.

- Brilliant visual alarm - 360° distinct alarm level, flash rates prioritised
- Ultra loud audible alarm - penetrating 95 dBA

- Plug 'n' Play sensor technology with an extensive range of gas sensors
- A unique combination of pump diffusion sampling. Specifically designed for pre-entry and post-entry applications.
- A robust, moulded, rubberised casing guaranteeing Hi-Viz and Hi-Impact resistance
- International certification and conformance

Measuring Ranges

LEL

O2
H2S
CO
H2S/CO
SO2
CL2
NO2
NH3
NO
CO2
LEL (IR))

0-100%

0-25%
0-100 ppm
0-1000 ppm
0-100 ppm/0-1000 ppm
0-30 ppm
0-10 ppm
0-20 ppm
0-100 ppm
0-300 ppm
0-5%
0-100%

Certification

Environment

ATEX

UL
IECEX
MED [⊙]

[Download Product Datasheet for Details](#)

Temperature Limits:

-4 deg.F to +104 deg.F

Humidity:

0-95% RH non-condensing

Alarms

Sampling System

Brilliant visual alarm
360° distinct alarm level

Ultra loud audible alarm, 95 dBA

Diffusion operation
Optional internal sampling pump

Physical Properties

Power Supply

Weight: 14 oz
Dimensions: 5.5 x 3.3 x 1.7 in.

Alkaline AA Cells
NiMH Re-Chargeable Pack

Battery Life:
Alkaline - Up to 24 Hours
(17 with pump)
Re-Chargeable - Up to 20 Hours
(14hrs with pump)

- Personal Safety in Confined Space - H2S/O2/CO Hazards
- General Safety in Confined Space
- Shipping - General
- Shipping - Fumigant
- Breweries - CO2 Hazard
- Plant Shutdown
- Permit to Work Systems
- Pressurised Tunnelling
- Fleet Auxiliary

[Product Datasheet](#)